



The MS-PE Series Inverter / Charger



The MS-PE Series pure sine wave inverter/charger

MODEL NUMBERS

- MS4124PE
- MS4348PE

AVAILABLE FOR

- Renewable Energy Systems
 - Off-grid Power
 - Back-up Power
- Marine Systems
- Caravan Systems
- Truck Systems

AVAILABLE ACCESSORIES

- MMP-E
- AGS
- Battery Monitor Kit
- Conduit Box
- Fuse Blocks
- MagWeb
- Remote - ME-ARC
- Remote - ME-RC
- Router
- Smart Battery Combiner

The MS-PE 230V Series Inverter/Charger from Magnum Energy is a pure sine wave inverter designed specifically for the most demanding renewable energy applications. The MS-PE Series is powerful, easy-to-use, and best of all, cost effective.

Parallel stacking: You can parallel up to four inverter/chargers for up to 17.2kw of power at 230V. The Magnum Router is required for parallel stacking the MS-PE Series.

Power Factor Corrected (PFC) Charger: Our PFC charger is built into all of our inverter chargers. It uses less energy from a generator than a standard charger – using 25-30% less AC current than standard chargers.

Safe and reliable: The MS-PE Series is listed to the stringent requirements CE for renewable energy installations.

Features

Pure sine wave: Power your T.V.s, stereos, plasma screens, and other sensitive electronics without worry. The pure sine wave inverter and power factor corrected charger provide clean, reliable inverter power with low total harmonic distortion (THD) of less than 5%.

Versatile mounting: Mount the MS-PE Series on a shelf or wall.

Lightweight: The lightweight aluminum base and cover also provides noise reduction and corrosion resistance.

Multiple ports: The MS-PE Series provides multiple ports, including an RS485 communication port for network expansion, and a remote port.

Accessible design: The extra large AC access cover with terminal screw block and 360° DC connection terminals with covers make this inverter more accessible when it needs to be.

Convenient switches: The MS-PE Series comes with an on/off inverter-mounted switch with an easy-to-read LED indicator.

Buy with ease: The MS-PE Series is backed by a two-year (24-month) limited warranty.



MS-PE Series Specifications

	MS4124PE	MS4348PE
Inverter Specifications		
Input battery voltage range	18 - 34 VDC	36 - 64 VDC
Nominal AC output voltage	230 VAC ±5%	230 VAC ±5%
Output frequency and accuracy	50 Hz ± 0.4 Hz	50 Hz ± 0.4 Hz
Total Harmonic Distortion (THD)	< 5%	< 5%
1 msec surge current (amps AC)	65	75
100 msec surge current (amps AC)	30	37
5 sec surge power (real watts)	6300	7500
30 sec surge power (real watts)	5300	7100
5 min surge power (real watts)	4750	6600
30 min surge power (real watts)	4600	5000
Continuous power output at 25° C	4100 VA	4300 VA
Maximum continuous input current	273 ADC	143 ADC
Inverter efficiency (peak)	90%	91%
Transfer time	~ 20 ms	~ 20 ms
Search mode (typical)	9 watts	10 watts
No load (230 VAC output, typical)	30 watts	28 watts
Waveform	Pure Sine Wave	Pure Sine Wave
Charger Specifications		
Continuous output at 25° C	105 ADC	55 ADC
Charger efficiency (peak)	88%	91%
Power factor	> .95	> .95
Input current at rated output (AC amps)	14	16
General Features and Capabilities		
Transfer relay capability	30 amps AC	
Five stage charging capability	Bulk, Absorb, Float, Equalize (requires remote), and Battery Saver™	
Battery temperature compensation	Yes, 4.6 m (15') Battery Temp Sensor standard	
Internal cooling	0 to 120 cfm variable speed drive using dual 92mm brushless DC fans	
Overcurrent protection	Yes, with two overlapping circuits	
Overtemperature protection	Yes on transformer, MOSFETS, and battery	
Conformal coating on PCB's for corrosion protection	Yes	
Powder coated chassis & top for corrosion protection	Yes	
Stainless steel fasteners for corrosion protection	Yes	
Listings	CE	
Warranty	Two years	
Environmental Specifications		
Operating temperature	-20° C to +60° C (-4° F to 140° F)	
Nonoperating temperature	-40° C to +70° C (-40° F to 158° F)	
Operating humidity	0 to 95% RH non condensing	
Physical Specifications		
Dimensions (l x w x h)	34.9 cm x 32.1 cm x 20.3 cm (13.75" x 12.65" x 8.0")	38.1 cm x 16.5 cm x 12.7 cm (15.0" x 6.5" x 5.0")
Mounting	Shelf (top or bottom up) or wall	Shelf (top or bottom up) or wall
Weight	25.0 kg (55 lb)	25.0 kg (55 lb)
Shipping weight	28.6 kg (63 lb)	28.6 kg (63 lb)
Max operating altitude	4570 m (15,000')	4570 m (15,000')

Magnum Energy, Inc.

2211 West Casino Road
Everett, Washington 98204 USA

The Powerful Difference

Phone: 425-353-8833
Fax: 425-353-8390
Web: www.magnumenergy.com

Testing for specifications at 25° C
Specifications subject to change without notice.

August 2012, Rev A

Part #64-0496

New Zealand
Independent Power (NZ) Ltd
Phone: 09 415 6686
Email: sales@indepower.co.nz